



UNIFOAM®

Custom-Cut Insulation Panel

Type 1, Type 2, Type 3, and Type 4

Applications

- Under and over concrete slabs
- Interior and exterior walls
- Interior and exterior foundation walls
- Roofs and ceilings

Benefits

- Easy to install
- Resistant to water and freeze-thaw conditions
- Excellent compressive strength
- Permanent insulating value that does not diminish over time

Technical Specifications

UNIFOAM®

Type 2



The expanded polystyrene used to manufacture UNIFOAM® is Intertek certified (ETL Listed) in accordance with ULC S701

Thickness

R-Value

1"	R4.00
1 1/4"	R5.00
1 1/2"	R6.00
1 3/4"	R7.00
1 7/8"	R7.50
2"	R8.00
2 1/2"	R10.00
3"	R12.00
4"	R16.00

Available Sizes

24" x 24"	24" x 96"	48" x 96"	48" x 108"
-----------	-----------	-----------	------------

*Other sizes and densities available.

Cut Profiles



Shiplap Cut
Thicknesses of 1" and greater



Drainage Cut
Thicknesses of 1" and greater



Square Cut
All thicknesses



Insert Cut
Thicknesses of 1" and greater



Tongue and Groove
Thicknesses of 1" and greater

